

TRUE GRIP® (46-GRIT)

PRODUCT INFORMATION GUIDE

Application(s): Anti-slip grit tape products are a fast, easy way to reduce slip and fall accidents in the workplace. Tape will adhere to any clean dry surface including metal, wood and concrete. Surface is constructed of a silicone carbide grit compound securely bonded to a vinyl substrate with an aggressive acrylic adhesive. Tape is available in black only. Intended for both indoor and outdoor applications, and is very water-resistance under normal conditions. Not intended for submerged applications.

Adhesive: Acrylic Solvent Adhesive

Carrier: Vinyl (6 mil) with Silicone Carbide Grit Material (46-Grit)

Total Thickness: 0.030" (0.762mm)

Grit Size: 46-Grit

Liner: Brown Kraft Paper Liner 0.007" (0.18mm)

Tape Application: Minimum application temperature 10⁰C (50⁰F)
Surface must be clean and free from dust, dirt, oil, wax, silicone.

Cleaning: Clean tape surface with a mild soap and light broom, rinse with fresh water.

Shelf Life: One year from date of purchase when stored at 70⁰F, 50% relative humidity.

Static Friction: 1.039 Dry Leather
ASTM D1894-06 1.210 Wet Rubber

Kinetic Friction 0.926 Dry Leather
ASTM D1894-06 1.050 Wet Rubber

Property:	Test Method:	Measurement:
PVC Film Thickness Tensile Strength MD Tensile Strength CD Elongation	PSTC-33 ASTM-D638 ASTM-D638 ASTM-D638	0.15mm (6 mils) 4.2 Kg/15mm (15.4 lbs/inch) 3.1 Kg/15mm (11.4 lbs/inch) 200% +/- 25%
Acrylic Adhesive Dry Coat Weight Coating Thickness Residual Solvent Tack	PSTC-33 PSTC-33 PSTC-6	44.4 g/m ² 0.06mm (0.0023") > 0.5%
Shear Resistance 180 Peel Adhesion Operational Temp. Min Application Temp.	PSTC-7 PSTC-1	20 cm (8 inch) 24 hours (1" x 1" @ 1 Kg) 2.5 Kg/25mm (5 lb/inch) (-10 ⁰ C to 60 ⁰ C) -14 ⁰ F to 140 ⁰ F 10 ⁰ C (50 ⁰ F)

MANUFACTURING GROUP way constitutes a specification, nor should it be seen as a recommendation for use. We accept no liability for any loss, damage
www.incomdirect.com or injury resulting from the use of these products or data.

August 2008.

[Click here to order - www.safety-tapes.com](http://www.safety-tapes.com)